

# SAVEEN MG 250/500 Specification

Capacity(GI)		kVA	250/500
AC input	Rated voltage	V	380(± 10%)
	Frequency	Hz	50 / 60
	Connection phase	-	3phase 4wire
AC Output (Load)	Rated voltage	V	380(± 10%)
	Frequency	Hz	50 / 60
	Phase	-	3phase 4wire
PCS(GI)	Rated voltage	V	380(± 10%)
	Frequency	Hz	50 / 60
	Phase	-	3phase 4wire
	Power factor(@rated)	-	0.99 이상
	cosφ range	-	0.7 ~ 1
	Voltage THD	%	< 3
	Voltage unbalance	%	< 3
	Efficiency	%	96.5
Transfer Time		ms	< 4(60Hz) / < 5(50Hz)
DC Input (Battery)	Rated voltage	V	570
	Operation range	V	570 ~ 830
	Backup time	min	> 30
etc	Cooling Method	-	Forced Air Cooling
	Ambient Temperature	℃	-10 ~ +40
	Max. height above sea-level	m	< 1000
	Humidity	%	0 ~ 95
	IP protection class	-	IP20
	Communication	-	Modbus TCP

\*상기 제품의 사양은 사정에 따라 변경될 수 있습니다.